



Never compromise on quality!

Published: November 2006

# PATINATION OIL

## Lead Surface Treatment

### Description

*A solvent based surface treatment for new lead sheet or flashings.*

### Uses

**PATINATION OIL** when correctly applied gives an evenness of colour to lead while its natural patina develops, it also prevents unsightly white staining.

### Preparation

The lead to be treated should be clean, dry and free from cement, dust and loose debris that may affect adhesion.

### Application

**PATINATION OIL** should be applied as soon as possible, immediately after each step of the lead work and certainly not later than the end of the working day.

1. Shake the can vigorously for at least 2 minutes before use and occasionally during application.
2. Apply the oil with a soft absorbent cloth.
3. Work horizontally from top to bottom maintaining a wet lower edge. **DO NOT USE A CIRCULAR SCRUBBING ACTION.**
4. Ensure application is complete before any rain.

### Limitations

Do not allow Patination Oil to come into contact with bituminous surfaces or polycarbonate sheet.

### Storage Conditions

Store in cool, dry conditions in a sealed container between 5 and 30°C.

### Shelf Life

12 months when stored according to manufacturers instructions in unopened containers.

### Coverage

Approximately 60m<sup>2</sup> per litre.

### Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations.

### Health & Safety

Paint related product UN1263

**Contains methyl ethyl ketoxime. May produce an allergic reaction. Contains white spirit low aromatic.**

- ◆ Flammable.
- ◆ Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- ◆ Repeated exposure may cause skin dryness or cracking.
- ◆ Keep out of reach of children.
- ◆ Keep away from sources of ignition - No smoking.
- ◆ Do not empty into drains.
- ◆ Dispose of this material and its container at hazardous or special waste collection points.
- ◆ In case of accident or if you feel unwell, seek medical attention immediately (showing label where possible).
- ◆ Use appropriate container to avoid environmental contamination.
- ◆ See separate material safety data sheet for full handling, use and storage.

**WARNING:** cloths contaminated with **PATINATION OIL** should be burnt after use as in certain conditions spontaneous combustion can occur caused by oxidation of the oil.

## Specification Summary

Appearance	Straw coloured liquid that dries clear
Flammability	Flammable
Boiling Point	152°C
Solubility in water	Insoluble
Flashpoint	38°C

### Container Sizes

<b>Code:</b>	BDPO05	BDPO1	BDPO2
<b>Size:</b>	500ml	1L	2L

*The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.*